



Inspection Checklist to Certify that a Non- Conforming Light Vehicle is Equipped for Street Use

Office Use Only

Title and Registration Bureau

1003 Buckskin Drive, Deer Lodge, MT 59722-2375 • Phone (406) 444-3661 Fax (406) 846-6039 • mvdtitleinfo@mt.gov

Every non-conforming light vehicle that will be operated on highways or roads allowing for vehicular traffic dedicated to public use in the state of Montana must be equipped with the following as required in MCA Title 61, chapter 9.

All boxes must be checked:

Head Lamps:

- At least two, one on each side of the front of the dune buggy or go-cart.
- Positioned not more than 54 inches nor less than 22 inches from the center of the lamps to the ground.
- High beam indicator/selector.
- High beam appears to be of such intensity to project 350 feet.
- Low beam appears to be of such intensity to project 100 feet.

Tail Lamps:

- Two mounted on rear of vehicle that emit a red light plainly visible from a distance of 1,000 feet to the rear.
- Positioned not more than 72 inches nor less than 15 inches from the ground.
- Either a tail lamp or a separate lamp must illuminate with a white light the rear license plate and render it clearly visible at a distance of 50 feet.
- Tail lamp and separate lamp for illuminating the rear license plate must be lighted whenever headlamps are lighted.

Reflectors:

- At least two red reflectors (separate or part of tail lamps).
- Positioned not less than 15 inches or more than 60 inches from the ground to center of the reflector.
- Appears to be visible from a distance of 50-300 feet.

Stop Lamps:

- Two functioning stop lamps.
- Red in color; may be incorporated into tail lamp.
- Appear to be visible from a distance of 300 feet in normal sunlight.

Horn:

- Cannot be unreasonably loud, harsh sounding or a whistle.
- Appears to be audible from a distance of at least 200 feet.

Mufflers:

- Muffler system to prevent excessive or unusual noise and annoying smoke.
- No cut-outs, bypasses or similar devices.

Windshield:

- Consists of safety glazing material meeting requirements of MCA 61-9-408.
- Must be equipped with device for clearing rain, snow or other moisture from the windshield.

Fenders, Splash Aprons or Flaps:

- Fenders extend in full width from a point above and forward of the center of the tires over and to the rear of the tires.
- Splash aprons or flaps extend downward in full width from a point not lower than halfway between the center of the tires and the top of the tires and to the rear of the tires.
- Fenders, splash aprons or flaps extend downward to a point not more than 20 inches above surface of highway when vehicle is empty.
- Extends to each side of the width of the tire or of a combined width of multiple tires.

Brakes:

- Equipped with brakes on all wheels; appear to be in good working condition.
- Equipped with parking brakes.

Seat Belts: Equipped with seat belts at each designated seating position.

Mirror: At least one mirror attached to vehicle to reflect to driver a view of the highway at least 200 feet to the rear.

Bumpers: Equipped with front and rear bumper.

Minimum Speed: Vehicles unable to travel more than 25 mph must display a slow-moving vehicle sign (MCA 61-9-415).

Check only ONE box: Tires - no metal tires allowed: Solid rubber tires, having rubber on entire traction surface 1 inch thick above edge of flange on the entire periphery. Low-pressure pneumatic tires.

Vehicle Description

Year	Make	Model	Body Style	No. of CCs	No. of wheels	Wheel Base	Wheel Diameter
License Plate No.		Expiration Date	Vehicle Identification Number			State of Registration	
Owner/Applicant Name							
Address				City/State/Zip			
I certify that I have physically inspected this non-conforming light vehicle and determined that the information provided is correct (use additional paper for remarks).							
Signature of Inspector						Date	
Printed Name of Inspector			Law Enforcement or Department Agency			Badge Number (if applicable)	